

Cembrit Holding A/S

Sohngaardsholmsvej 2 PO Box 750 DK-9100 Aalborg Denmark

Reg. no 18336774

info@cembrit.com

www.cembrit.com

Declaration of Performance Tel.: +45 99 37 22 22 Fax: +45 99 37 23 22 No. 023/DoP

In accordance with Regulation (EU) No 305/2011 of the European Parliament and of the Council laying down harmonised conditions for the marketing of construction products (CPR EU 305/2011)

I. Unique identification code of product-type:

Fibre-cement profiled sheets

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4).

Cembrit W177-5,5 RC, Cembrit W177-6,5 RC

Profile 177/51, Thickness 6,5 mm, Impact Resistant (B55 RC, B65 RC, A6, A6, 5, B9 RC, CEMFORT B55, CEMFORT B65, RC - P5, RC - P6)

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roofing. Internal wall finishes. External wall and ceiling finishes

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article II (5):

> Cembrit Holding A/S Sohngaardsholmsvej 2 **PO Box 750** DK-9100 Aalborg, Denmark Email: info@cembrit.com

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

Not Applicable

5. System or system of assessment and verification of constancy of performance of the construction product as out in Annex V:



6a. Name and identification number of the notified body (in case of the declaration of performance concerning a construction product covered by a harmonised standard):

Technical and Testing Institute of Construction Prague, s. p., Notified body No. 1020 Branch 0700- Ostrava, U Studia 14, 700 30, Ostrava-Zábřeh, Czech Republic

Performed initial type- and acceptance testing according to system 3, EN12467. Test report No. 1020-CPD-070030732 of February 8, 2007

PAVUS, a.s. Notified body No. 1391 Prosecká 412/74, 190 00 PRAHA 9 - Prosek, Czech Republic

Performed reaction to fire testing and classification according EN 13501-1. Test report No. PK1-01-07-010-E-1 (colored variants), dated December 8th, 2016 and No. PK1-01-07-011-E-1 (non-colored variants) dated December 8th, 2016.

6b. Name and identification number of the Technical Assessment Body (in case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued):

Not applicable

7. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Type of sheets	NT	
Mechanical resistance	CIX	
Breaking load	Min. 4,25 kN/m	
Bending moment	Min. 55 Nm/m	
Apparent density	min I 400 kg/m³	
Impact resistance	Pass	
External fire performance	B _{ROOF} (deemed to satisfy)	
Reaction to fire	Class A I	
Water impermeability	Pass	EN 494:2012+A1:2015
Dimensional variations		Fibre-cement profiled sheets
Length	± 10 mm	and fittings.
Width	+ 10 / - 5 mm	Product specification
Thickness	6,5 ± 0,6 mm	and test methods
Height of the corrugations	51 ± 3 mm	
Pitch	177 ± 2 mm	
Squareness	max 6 mm/m	
Release of dangerous substance	No performance determined	
Durability against warm water	R _L ≥ 0,7	
Durability against soak/dry	R _L ≥ 0,7	
Durability against freeze-thaw	R _L ≥ 0,7	
Durability against heat-rain	Pass	



8. Appropriate Technical Documentation and/or Specific Technical Documentation:

EN 494:2012+A1:2015 Fibre-cement profiled sheets and fittings. Product specification and test methods

The performance of the product identified in points I and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Esben Moos, Group Technical Manager Aalborg, April 4th, 2017