

Declaration of Performance No. 028/DoP

In accordance with Regulation (EU) No 305/2011 of the European Parliament and of the Council laying down harmonised conditions for the marketing of construction products (CPR EU 305/2011)

1. Unique identification code of the product-type:

Fibre-cement profiled sheets and fittings

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Cembrit W177-6, Cembrit W177-6,5

**Fibre-cement profiled sheets - NT, profile 177 mm/51 mm, thickness 6,5 mm
(B9, B60, B65, EuroFala B65)**

Fibre-cement fittings - NT, thickness 6 mm or 4 mm

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roofing

Internal wall finishes - External wall and ceiling finishes

3. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

**Cembrit Holding A/S
Sohngaardsholmsvej 2
PO Box 750
DK-9100 Aalborg, Denmark
Email: info@cembrit.com**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

- 6a. Name and identification number of the notified body (in case of the declaration of performance concerning a construction product covered by a harmonised standard):

**Centralny Ośrodek Badawczo-Rozwojowy Przemysłu Izolacji Budowlanej
Korfantego 193, 40-157 Katowice, Poland
Notyfikowana jednostka Nr. 1486**

Performed Initial Type Test under system 3, according to EN 494. Test reports No. 47/09/137/WC-1, 48/09/138/WC-1, 49/09/139/WC-1, 77/06/1/192/WC-2.

**Instytut Techniki Budowlanej – Zakład Badań Ogniwych
Ksawerów 21, 02-656 Warszawa, Poland
Notyfikowana jednostka Nr. 1488**

Performed reaction to fire testing and classification according EN 13501-1. Classification Report No. 0771.1-10-Z00NP (English version of Classification report No NP-3639.1/09/KP) for unpainted sheets (A1), Classification report No 2721.3/03/10/Z00NP/U (English version of Classification report. No 2721.1/03/10/Z00NP/U) for painted sheets (A2, s1, d0) and report No. 163/06.

- 6b. Name and identification number of the Technical Assessment Body (in case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued):

Not applicable

7. Declared performance:

Cembrit NT - Profile 177 mm/51 mm, thickness 6,5 mm			
Essential characteristics	Performance		Harmonised technical specification
Type of sheets	NT		EN 494:2012+A1:2015 Fibre-cement profiled sheets and fittings – Product specification and test methods
Apparent density	min. 1400 kg/m ³		
Mechanical resistance	Short sheets: Length < 0,9 m	C	
	Bending moment	Min. 30 Nm/m	
	Long sheets: Length > 0,9 m	C1X	
	Breaking load Bending moment	min. 4250 N/m min. 55 Nm/m	
Impact resistance	No Performance Determined		
External fire performance	B _{ROOF} (deemed to satisfy)		
Reaction to fire	unpainted sheets	A1	
	painted sheets	A2-s1, d0	
Water permeability	Pass		
Dimensional variations	Pass		
	length	± 10 mm	
width	+ 10 mm / -5 mm		

thickness	6,5 mm ± 0,6 mm
height of corrugations	51 mm ± 3 mm
pitch	177 mm ± 2 mm
out of squareness	≤ 6 mm
Release of dangerous substance	No Performance Determined
Durability against warm water	Pass - $R_L \geq 0,7$
Durability against soak - dry	Pass - $R_L \geq 0,7$
Durability against freeze - thaw	Pass - $R_L \geq 0,7$
Durability against heat - rain	Pass

Fibre-cement fittings - NT, thickness 6 mm or 4 mm			
Essential characteristics	Performance	Harmonised technical specification	
Type of fittings	NT	EN 494:2012+A1:2015 Fibre-cement profiled sheets and fittings – Product specification and test methods	
Apparent density	min. 1300 kg/m ³		
Reaction to fire	unpainted fittings		A1
	painting fittings		A2-s1, d0
Dimensional variations	Pass		
length	± 10 mm		
width	± 10 mm		
thickness	± 1 mm		
Release of dangerous substance	No Performance Determined		
Durability against freeze - thaw	Pass		

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

EN 494:2012+A1:2015
Fibre-cement profiled sheets and fittings
Product specification and test methods

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Esben Moos, Group Technical Manager
Aalborg, April 4th, 2017



.....